

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	01/07/2016	J. LEE

DESCRIPTION: 22 AWG, 4 CONDUCTOR, PVC INSULATION, ALUMINUM / MYLAR FOIL SHIELD
WITH A 22 AWG STRANDED DRAIN WIRE AND AN OVERAL PVC JACKET.

CONDUCTORS: 22 AWG (7X30) TINNED COPPER

INSULATION: PVC - POLYVINYL CHLORIDE

INSULATION WALL THICKNESS: 0.016"

INNER WIRE INSULATION COLORS:

1. BLACK
2. BROWN
3. BLUE
4. WHITE

NOMINAL LAY LENGTH OF TWISTED INNER WIRES: 2.25" (LEFT HAND LAY) APPROX. FIVE (5) TWISTS PER FOOT.

SHIELD: ALUMINUM / MYLAR - 100% COVERAGE

DRAIN WIRE: 22 AWG (7X30) TINNED COPPER

JACKET: PVC - POLYVINYL CHLORIDE

JACKET COLOR: BLACK

WALL THICKNESS: 0.030"

OVERALL DIAMETER: 0.207"

RIP CORD: YES

WEIGHT: 28 LBS PER 1,000 FEET

UL AWM RATING: 2517


VOLTAGE RASTING: 300V (RMS)

TEMPERATURE RATING: 105C

ROHS COMPLIANT: YES

REACH COMPLIANT: YES

MADE IN THE UNITED STATES

ITEM NO.	QTY REQ'D	PART NUMBER	DESCRIPTION				
DO NO SCALE THIS DRAWING		DRAWN BY	DATE	 SILVER STATE WIRE & CABLE WWW.SILVERSTATEWIRE.COM			
ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED TOLERANCE: ANGLES ± 0.5° DEC. .XX ± 0.03 DEC. .XXX ± 0.010		D. MILLER	01/07/2016				
		CHECKED BY	DATE				
		J. LEE	01/07/2016				
THIS DRAWING IS THE PROPERTY OF SILVER STATE WIRE & CABLE AND SHALL NOT BE REPRODUCED, COPIED, OR USED AS THE BASIS FOR THE MANUFACTURE OR SELL OF THIS DESIGN WITHOUT THE WRITTEN PERMISSION OF SILVER STATE WIRE AND CABLE.		APPROVED BY	DATE	DESCRIPTION			
		J. LEE	01/07/2016	24 AWG, 4 COND, FOIL, PVC, UL 2517, 300V, 105C			
		APPROVED BY	DATE	SIZE	CAGE CODE	DWG NO.	REV
		N/A	N/A	A	01CV1	S-4367-3787	A
				SCALE	NONE	WT	SHEET 1 OF 1