REVISIONS					
REV	DESCRIPTION	DATE	APPROVED		
Α	RELEASE	08/05/2020	J. LEE		

D

С

В

Description: 26 AWG 10 Conductors 7 strands tinned copper wire, PVC insulation, shielded, and a PVC, jacket. AWM 2464 80°C 300V or CSA

Conductor AWG Size & Stranding: 26 AWG 7 Strands Class B Material: Annealed Tinned Copper Conductor Count: 10 Conductors Insulation Material: Polyvinylchloride Insulation Wall Thickness: 0.010" Insulation Diameter: 0.038" ± 0.002" Insulation Color Code: Black, Brown, Red, Orange, Yellow, Green, Blue, Purple, Gray, White

Nominal Lay Length: 2.25" LHL (5.33 tw/ft) Shielded: Aluminum / Mylar – 100% Coverage Drain Wire: 26 AWG 7 Strands Tinned Copper

Jacket Material: Tubed Polyvinyl-Chloride Jacket Wall thickness: 0.032" Jacket Diameter: 0.219" ± 0.020" Jacket Color: Black Jacket Ripcord: Yes Jacket Weight: 29 Lbs / Mft Jacket Markings: Cable permanently identified via surface ink-jet print Footage Markers: Yes

Standards:

UL recognized component as AWM 2464 per UL standard 758 For internal wiring or external interconnection of electronic equipment CSA listed as AWM, Class I or II, Group A or B, per CSA Standard C22.2 No. 210-15 Cable meets RoHS 2002/95/EC Directive, RoHS 2 2011/65/EU Directive, RoHS 3 2015/863/EU Directive Cable is REACH compliant per Regulation (EC) No 1907/2006 (197) Updated January 15, 2019 Operating Voltage: 300V RMS Maximum Made in the USA

4

WARNING: This product may contain chemicals, such as Vinyl Chloride, known to the state of California to cause cancer. For more information, go to www.P65Warnings.ca.gov. Wash hands after handling

3

ITEM NO. QTY REQ'D PART	IUMBER				DESCRIPTION					
DO NO SCALE THIS DRAWING	DRAWN BY		DATE							
ALL DIMENSIONS ARE IN INCHES UNLES OTHERWISE SPECIFIED	, D. MIL	D. MILLER		SSVL						
TOLERANCE:	CHECKED BY		DATE	SILVER STATE WIRE & CABLE				ļ		
ANGLES $\pm 0.5^{\circ}$ DEC, XX ± 0.03	J. LEE	J. LEE 08/05/		WWW.SILVERSTATEWIRE.COM						Ĺ
DECXXX ± 0.010	APPROVED B	(DATE	DESCRIF						
THIS DRAWING IS THE PROPERTY OF	J. LEE		08/05/2020	26 /	26 AWG, 10 COND, CABLE					
SILVER STATE WIRE & CABLE AND SHA NOT BE REPRODUCED, COPIED, OR USE	<u> </u>		DATE	SIZE	CAGE CO	ODE	DWG NO.		REV	
AS THE BASIS FOR THE MANUFACTUR OR SELL OF THIS DESIGN WITHOUT TH		approved by N/A		A	01C\	/1	J-0830-0	0127	Α	
WRITTEN PERSMISSION OF SILVER STAT WIRE AND CABLE	E N/A			SCALE	NONE	WT		SHEET 1	0F 1	
		2					1			-

5