	CONSTRUCTION DETA	AILS				
INNER CONDUCTOR: 22 AWG, STRANDED,		DED, SILVER PLATED COPPER				
NNER CONDUCTOR INSULATION	EXTRUDED FLUC 0.004 INCHES	EXTRUDED FLUOROPOLYMER, 0.050 INCH OD, +/- 0.004 INCHES				
NNER CONDUCTOR COLOR:	WHITE	WHITE				
SHIELD:	SILVER PLATED (SILVER PLATED COPPER, 85% MINIMUM COVERAGE				
ACKET:	TAPE WRAPPED	PTFE, WHITE				
ACKET OVERALL DIAMETER:	0.092 INCHES, +/-	- 0.004 INCHES				
	ORMANCE / CHARATE					
ERMPERATURE RATING:	-55°C to +200°C					
/OLTAGE:	600 VOLTS RMS					
VEIGHT:	9.69 LBS PER 1,0					
ENVIRONMENTAL:	ROHS COMPLIAN	NT .				
MPEDANCE (OHMS):	27 (+/- 4)					
/ELOCITY OF PROPAGATION:	70					
CAPACITANCE (pF/ft):	55					
	- 6/27/2010	New Release	THE SECOND : -	UE PROPERTY OF ALL VERY COLUMN		
F	A 12/14/2014	12/14/2014 DETAILS		HE PROPERTY OF SILVER STATE WIRE & HALL NOT BE REPRODUCED, COPIED, OR FOR THE MANUFACTURE OR SALE OF THIS	55WC	
SNC			DESIGN WITH OUT TH	E WRITTEN PERMISSION OF SILVER STATE WIRE & CABLE, INC.	33VVL	
REVISIONS						
REV				LANE =	50 E. Greg Street, Sparks, NV. 89431	
	+		DRAWN BY: J. LEE	E22-1-STJ	PH:775-356-8969 FAX: 775-356-3948	
			DRAWING NO:		111.775-555-5555 17-78.775-555-5546	