

# Flexi-Lene 105

## High Flex 32AWG Insulated Wire

PART NUMBER	AWG	STRANDING		CONDUCTOR DIAMETER	INSULATION TYPE	INSULATION COLOR	FINISHED INSULATED DIAMETER (NOM.)
		COUNT	/ AWG				
S-7244-5471	32	19	/ 44	0.010" (0.254mm)	FLEXIBLE PVC	BLACK	0.023" (0.584mm)
S-7244-6591	32	19	/ 44	0.010" (0.254mm)	FLEXIBLE PVC	BROWN	0.023" (0.584mm)
S-7244-6854	32	19	/ 44	0.010" (0.254mm)	FLEXIBLE PVC	RED	0.023" (0.584mm)
S-7244-6547	32	19	/ 44	0.010" (0.254mm)	FLEXIBLE PVC	ORANGE	0.023" (0.584mm)
S-7244-1987	32	19	/ 44	0.010" (0.254mm)	FLEXIBLE PVC	YELLOW	0.023" (0.584mm)
S-7244-5897	32	19	/ 44	0.010" (0.254mm)	FLEXIBLE PVC	GREEN	0.023" (0.584mm)
S-7244-3547	32	19	/ 44	0.010" (0.254mm)	FLEXIBLE PVC	BLUE	0.023" (0.584mm)
S-7244-1986	32	19	/ 44	0.010" (0.254mm)	FLEXIBLE PVC	VIOLET	0.023" (0.584mm)
S-7244-4981	32	19	/ 44	0.010" (0.254mm)	FLEXIBLE PVC	GREY	0.023" (0.584mm)
S-7244-0878	32	19	/ 44	0.010" (0.254mm)	FLEXIBLE PVC	WHITE	0.023" (0.584mm)

More flexible PolyvinylChloride Insulation

**STRIPING**  
 STRIPING is available upon request; Please contact us for details and part number assignment for your requested color.

PERFORMANCE	
VOLTAGE	UP TO 300 VOLTS
COLD BEND	CONDITION 4 HOURS @ - 60° C
TEMPERATURE RATING	- 40° C to + 90° C
ROHS COMPLIANT	YES
INSULATION WALL THICKNESS	0.007"

REVISIONS	REV	DATE	BY	NOTES
	-	4/10/2010	JEL	NEW RELEASE
	A	9/4/2013	RTL	ADDED COMPOUND, PRINT
	B	2/15/2016	JEL	UPDATED COLORS

THIS DRAWING IS THE PROPERTY OF SILVER STATE WIRE & CABLE AND SHALL NOT BE REPRODUCED, COPIED, OR USED AS THE BASES FOR THE MANUFACTURE OR SALE OF THIS DESIGN WITH OUT THE WRITTEN PERMISSION OF SILVER STATE WIRE & CABLE

APPROVED BY: J. LEE  
 DRAWN BY: R. LANE  
 DRAWING NO: **S-7244**



50 E. Greg Street, Sparks, NV. 89431  
 PH: 775-356-8969 FAX: 775-356-3948  
 WWW.SILVERSTATEWIRE.COM