

UL1015

UL 1015, UL Style 1015, AWM 1015
UL and CSA Style TEW, MTW Hook Up Wire
UL Style 1015 600V 105°C
UL Style 1032 1000V 90°C
UL Style 1230 600V 105°C Dry; 60°C Wet
CSA Type TEW 600V 105°C
Passes UL VW-1 Flame Test
Marine approvals for 10 AWG - 16 AWG: UL Standard 1426

Description:

Conductor: Stranded or Solid
Insulation: Poly Vinyl Chloride (PVC)
Nominal Insulation Thickness: 0.031"
Temperature Range: -20°C to +105°C
Voltage Rating: 600 Volts
Applications: May be used for the internal wiring of appliances, for the internal wiring of appliances where exposed to oil at a temperature not exceeding 60°C or 80°C.

Standard Color Code		
0	-	BLACK
1	-	BROWN
2	-	RED
3	-	ORANGE
4	-	YELLOW
5	-	GREEN
6	-	BLUE
7	-	VIOLET
8	-	GREY
9	-	WHITE
P	-	PINK
T	-	TAN

Substitute the X in the Part Number for the desired color from the color code chart. For stripes add up to three color designations. Example: 092 would be Black with a White and a Red Stripe

Part Number	AWG Size	Stranding	Nom OD (in)	Approx LBS/1000 FT
UL101526126X	26	Solid	0.080	3.91
UL101526734X	26	7/34	0.083	4.00
UL101524124X	24	Solid	0.084	4.97
UL101524732X	24	7/32	0.088	5.11
UL101522122X	22	Solid	0.089	6.04
UL101522730X	22	7/30	0.095	6.27
UL101520120X	20	Solid	0.096	7.59
UL1015201030X	20	10/30	0.100	7.60
UL101518118X	18	Solid	0.104	10.10
UL1015181630X	18	16/30	0.110	10.16
UL101516116X	16	Solid	0.115	14.12
UL1015162630X	16	26/30	0.124	14.36
UL101514114X	14	Solid	0.128	19.83
UL1015144130X	14	41/30	0.141	20.10
UL101512112X	12	Solid	0.145	29.23
UL1015121930X	12	19/30	0.156	27.05
UL1015126530X	12	65/30	0.160	29.66
UL101510110X	10	Solid	0.164	39.70
UL10151010530X	10	105/30	0.194	42.20

REVISIONS	1/12/2011		New Release	

THIS DRAWING IS THE PROPERTY OF SILVER STATE WIRE & CABLE, INC. AND SHALL NOT BE REPRODUCED, COPIED, OR USED AS THE BASES FOR THE MANUFACTURE OR SALE OF THIS DESIGN WITH OUT THE WRITTEN PERMISSION OF SILVER STATE WIRE & CABLE, INC.

APPROVED BY: J. LEE
 DRAWN BY: R. LANE

DRAWING NO: **1015**



50 E. Greg Street, Sparks, NV. 89431
 PH: 775-356-8969 FAX: 775-356-3948
 WEB SITE: WWW.SILVERSTATEWIRE.COM