

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	NEW RELEASE	01-01-2020	J. LEE

SSWC PART NUMBER: B163S

MATERIAL: SILVER PLATED COPPER PER ASTM B298  
 NICKEL PLATING THICKNESS: 40 MICRO INCHES (MINIMUM)

(TUBULAR) NOMINAL INSIDE DIAMETER: 0.0781 INCHES ( 1.98 MM )

(LAYED FLAT) NOMINAL THICKNESS: 0.020 INCHES ( 0.51 MM )  
 (LAYED FLAT) NOMINAL WIDTH: 0.125 INCHES ( 3.17 MM )


AWG OF INDIVIDUAL STRAND ENDS: 36 AWG ( 0.005 INCH )

NUMBER OF STRANDS (CARRIERS): 24  
 NUMBER OF WIRES PER CARRIER: 3  
 TOTAL NUMBER OF INDIVIDUAL WIRE ENDS: 72

APPROXIMATE AWG SIZE OF FINISHED BRAID (TOTAL): 18 AWG  
 NOMIONAL CIRCULAR MILS: 1800  
 CURRENT CARRYING CAPACITY (AMPS): 16 AMPS  
 APPROXIMATE SHIPPING WEIGHT PER 1,000 FEET: 9 LBS  
 TEMPERATURE RATING: NOT TO EXCEED 200°C

ROHS COMPLIANT: YES  
 REACH COMPLIANT: YES  
 MADE IS THE UNITED STATES

STORAGE: MOISTURE FREE, SEALED BAG WITH DESICCANT / HUMIDITY INDICATOR (10% TO 60%)

DO NOT SCALE THIS DRAWING		DRAWN BY		DATE		 www.silverstatewire.com			
ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED  TOLERANCE: ANGLES ± 0.5° DEC. .XX ± 0.03 DEC. .XXX ± 0.010		D. MILLER		01/01/2020					
		CHECKED BY		DATE					
		J. LEE		01/01/2020					
THIS DRAWING IS THE PROPERTY OF SILVER STATE WIRE & CABLE AND SHALL NOT BE REPRODUCED, COPIED, OR USED AS THE BASIS FOR THE MANUFACTURE OR SELL OF THIS DESIGN WITHOUT THE WRITTEN PERMISSION OF SILVER STATE WIRE AND CABLE.		APPROVED BY		DATE		DESCRIPTION			
		J. LEE		01/01/2020		5/64 INCH, TUBULAR, SPC, BRAID			
		APPROVED BY		DATE		SIZE	CAGE CODE	DWG NO.	REV
		-		-		A	01CV1	B163S	A
						SCALE	NONE		WT
								SHEET 1 OF 1	